

MODEL	CAPACITY (Tons)	TABLE SIZE (MM)	RAM SIZE (MM)	STROKE (MM)	DAY LIGHT (MM)	SHUT HEIGHT (MM)	SPEED (MM/SEC)			MOTOR (H.P.)	NO.OF CYLINDER	WORKING HEIGHT	Cushion Capacity	Cushion Stroke	Weight of M/C (Approx) Tons
							APPROACH	PRESSING	RETURN						
SHD-50+15	50	650X600	550X500	400	500	100	40	6-8	55	7.5	1+1	750	15	50	4.5
SHD-80+20	80	700X650	600X550	400	500	100	45	6-8	60	7.5	1+1	750	20	50	5.5
SHD-100+25	100	750X700	650X600	450	600	150	45	8-10	75	7.5	1+1	750	25	100	6.5
SHD-125+30	125	750X750	650X650	450	600	150	45	8-10	75	10	1+1	750	30	100	7.2
SHD-150+40	150	850X850	750X750	500	650	150	45	8-10	80	15	2+1	750	40	125	8.5
SHD-200+50	200	950X950	850X850	550	750	200	50	8-10	80	20	2+1	750	50	150	9.5
SHD-250+60	250	1000X950	900X850	550	750	200	50	8-10	80	25	2+1	750	60	175	11
SHD-300+70	300	1000X950	900X850	600	800	200	50	8-10	80	30	2+1	750	70	200	13
SHD-350+80	350	1000X1000	900X900	600	850	250	50	8-10	80	30	2+1	750	80	225	16
SHD-400+100	400	1000X1000	900X900	600	850	250	55	8-10	85	35	2+1	750	100	250	17.5
SHD-500+125	500	1000X1000	900X900	700	950	250	55	8-10	85	35	2+2	750	125	250	19
SHD-600+150	600	1200X1000	1000X900	700	1000	300	55	8-10	85	40	2+2	800	150	275	22
SHHP-700+175	700	1250X1000	1100X900	800	1100	300	55	8-10	85	45	2+2	800	175	300	24 to 28
SHD-800+200	800	1500X1200	1250X1000	850	1250	400	55	8-10	85	50	2+2	800	200	300	29 to 32
SHD-900+225	900	1500X1200	1250X1000	900	1300	400	55	8-10	85	50	3+2	800	225	350	34 to 36
SHD-1000+250	1000	1500X1200	1250X1000	900	1400	500	55	8-10	85	60	3+2	800	250	350	40 to 45
SHD-1200+300	1200	2000X1500	1600X1200	1000	1500	500	60	8-10	85	60	3+3	800	300	400	48 to 55
SHD-1500+375	1500	2000X1500	1600X1200	1000	1500	500	60	8-10	85	70	3+3	800	375	400	60 to 65